

Lovibond® Water Testing

Tintometer® Group



MD150 Chlorine, pH, powder reagents

Your daily companion for water analysis



- Wireless (NFC) and wired (USB-C) data transfer options
- Free Software and App for easy data management
- Intuitive user interface with easy-use icons and animations
- Exceptional durability to withstand demanding conditions

Part Number: 282105

The MD150 has several key features that make it a favourite among users.

— Multiparameter combinations

The MD150 provides essential parameters for pool water monitoring and disinfection control, including Chlorine, Bromine, Ozone, Chlorine Dioxide, pH, Cyanuric Acid, Alkalinity, and Calcium Hardness.

— Factory programmed methods

The MD150 comes with pre-programmed methods for pool and various other applications, ready to use out of the box.

— Flexible reagent options: compatible with tablets, powder or liquid

Compatible with various reagent types, simply select your preferred reagent in the settings, and the method list will display only the relevant options.

— Built for durability

The MD150 features a durable design with rubber-protected sides ensuring reliability even in demanding environments. With its IP67 rating, the instrument offers full protection against dust and water immersion.

— Ergonomic design

The MD150 is a compact, handheld instrument ideal for the use of the poolside, in the field, or in the lab. Its compact size and side protections ensure a firm grip, while rubber feet prevent slipping, enabling for single-handed operation.

— Quick and accurate results

The innovative optical system of the MD150 provides exceptional accuracy and fast results, delivering precise measurements in record time.

— One-Time-Zero function

Save operation time with the One-Time-Zero function, which remains valid for 8 hours unless the instrument is turned off

— Data transfer – NFC / USB-C

Easily transfer data wirelessly via NFC to the AquaLX® app or via USB-C cable to Lovibond® Data Expert. Data can be exported in CSV format for use in programs like Excel.

— GLP (Good Laboratory Practice) compliance

The MD150 automatically records and saves a protocol for every change, ensuring data quality and integrity by tracking any adjustments that could impact measurement results.

— Automatic data storage

The MD150 automatically stores the last 100 readings and protocols with a time/date stamp and retains the data even during battery changes.

— Keep your instrument up to date

Easily update the firmware and methods in seconds using Lovibond® Data Expert. Updates are available on the instrument's webpage.

— User defined method

With the free of charge Lovibond® Data Expert, you can create custom methods.

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Domestic | Pool Public | Pool Services | Power and Energy

Application

Boiler Water | Cooling Water | Disinfection Control | Drinking Water Treatment | Pool Water Control | Raw Water Treatment | Waste-Water Treatment

MD150 Chlorine, pH, powder reagents

The MD150, building on the legacy of the proven MD100 photometer, offers even more high-quality features and ease of use. Whether you're monitoring pool water or managing other water treatment needs, the MD150 provides versatile multiparameter combinations. With enhanced high-precision optics, the MD150 delivers unmatched accuracy and efficiency, making it the ideal solution for various water testing needs.

Measuring Range

Test Name	Measuring Range	Chemical Method
Chlorine HR 2 PP	0.1 - 10 mg/L Cl ₂	DPD
Chlorine HR T	0.1 - 10 mg/L Cl ₂ ^{a)}	DPD
Chlorine L	0.02 - 4.0 mg/L Cl ₂ ^{a)}	DPD
Chlorine PP	0.02 - 2 mg/L Cl ₂ ^{a)}	DPD
Chlorine T	0.02 - 6.0 mg/L Cl ₂ ^{a)}	DPD
pH value L	6.5 - 8.4 pH	Phenol Red
pH-value T	6.5 - 8.4 pH	Phenol Red

Technical Data

Optics	LED, spectrometer sensor, interference filter (only MD50 selected variants)
Light Source	LED
Wavelength	Variant specific (415, 445, 480, 515, 530, 555, 590, 630, 680)
Photometric Range	0 - 3 Abs
Suitable Vials	Round Cuvettes 13 mm Round Cuvettes 16 mm Round Cuvettes 24 mm
Display	Backlit LCD
Interfaces	USB-C NFC (Near Field Communication)
Data Transfer Format	.csv
Operation	Foil keypad
Auto – OFF	Yes
Programmability	yes with Lovibond Data Expert software
Calibration	Factory and user adjustment - return to factory adjustment possible at any time
Updates	Firmware and methods update
Internal Storage	Internal ring memory for 100 data records
Power Supply	2 x AA batteries Alkaline Batteries (LR6) 3V DC / 55mA
Battery Life Time	approx. 5000 measurements (without backlight)
Portability	Portable
Degree of Pollution	2
Maximum altitude above sea level	3500 m
Environmental Conditions	5 - 50 °C at a relative humidity of 30 - 95 % (non-condensing)
Protection Class	IP 67

Compliance	CE
Languages Full User Manual	English, German, Spanish, French, Portuguese, Italian, Dutch, Turkish, Chinese
Dimensions	155 x 76 x 45 mm
Weight	247 g

Delivery Scope

- 1 Instrument in Carrying case
- 100 Chlorine Free Powder Packs
- 100 Chlorine Total Powder Packs
- 100 tablet reagents Phenol Red Photometer
- 2 batteries (AA)
- 3 round cuvettes (glass) with lid and Sealing rings
- 1 Screwdriver
- 3 Stirring rods
- 1 Syringe 10 mL
- 1 Cleaning brush
- 1 USB-C to USB-A cable
- 1 Instruction manual
- 1 Certificate (COC)
- 1 Warranty information

Title	Part Number
Water sampler with bottle 250 mL and lid for MD50/MD150, AF 631	170500
Round cuvette 24 mm ø, set of 12	197620
Sealing ring for round vials 24 mm ø, set of 12	197626
Round cuvette 24 mm ø, set of 5	197629
Cleaning cloth	197635
USB-C cable 1 m, USB-C to A	19820-081
Verification Standard Kit MD50/MD150	215700
Stirring rod, 13 cm length	364100
Stirring rod, 10 cm length	364109
Stirring rod, 13 cm length, set of 10	364120
Stirring rod, 10 cm length, set of 10	364130
250 mL bottle, AF 631	375072
Brush, 11 cm length	380230
Measuring beaker, 100 ml	384801
Cuvette stand for 6 round cuvettes Ø 24 mm	418951
Plastic funnel with handle (white)	471007
ValidCheck Chlorine 1,5 mg/l	48105510

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C.
No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care China Tel.: 4009021628
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,
Lebuh Nilam 2, Bandar Bukit Tinggi,
Klang, 41200, Selangor D.E
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain

Technical changes without notice

Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies